



## Blueye Keyfob Q5

Specials:	The Keyfob is delivered	d on boxes of 100 piec	ces.	
Resistance:	The Keyfob is designed to resist common stress known from access control and time and attendance systems.			
Mechanical:	Drop test 10 times 10 cycles (1.8m)			
Immersion:	Water IP 67 (IEC 60529)			
Thermal:	-30°C and + 80 °C			
Material:	Polycarbonate.			
Electrical:	Operating Frequency:	125 kHz	± 6 kHz	
	Color:	Transparent Blue		
	Weight:	TBD g	± 0.50 g	
	Width:	28.60 mm	± 0.50 mm	
Physical:	Thickness: Length:	6.80 mm 47.40 mm	± 0.50 mm ± 0.50 mm	
IC type:	Q5 configured in RF/64	ASK Manchester		
10 6	OF configured in DE/CA	I ACI/ Manahaatan		
<u>Description</u>	Configurable, Keyfob with 224 bits user data memory design to suit to most 125 kHz proximity systems.			

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com

An ASSA ABLOY Group company

ASSA ABLOY Group company

<sup>®</sup> SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.2.12 - V2 - 25.08.2003 - Released - DefKey: 10419