



Clamshell Card UNIQUE

<u>Description</u>	1,5 mm thick Proximity Clamshell card design to suit to most 125 kHz proximity systems			
IC type:	UNIQUE 64 bits RF/64 ASK Manchester.			
Physical:	Thickness:	1.60 mm	± 0.40 mm	
	Width:	54.00 mm	± 0.40 mm	
	Length:	85.80 mm	± 0.40 mm	
	Weight:	7.80 g	± 0.50 g	
	Color:	White		
Electrical:	Operating Frequency:	125 kHz	± 6 kHz	
			'	<u> </u>
Material:	Hard shell: = ABS; Cover foil: = PVC			
	, , , , , , , , , , , , , , , , , , , ,			
Thermal:	-35°C to + 65 °C			
moman	00 0 10 1 00 0			
Resistance:	The card is designed to	rociet common et	rose known from accoss	s control and time and
Resistance: The card is designed to resist common stress known from access control attendance systems.				s control and time and
	attendance systems.			
Specials:	For volume of > 50K ni	aces the cards cou	ıld he ordered with a cu	stomized printing on the
Specials.	For volume of > 50K pieces the cards could be ordered with a customized printing on the back side foil. For volume of > 250K a customized log0 could be embossed in the cover shell			
	Back side foli. I of Voldi	110 01 - 2001C a Cu	stornized logo could be	CHIDOSSEA III THE COVER SHEII
Part number:	601403			
i ait number.	001403			

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com

An ASSA ABLOY Group company

ASSA ABLOY Group company

[®] SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.

CLF 3.3.2.3 - V1 - 11.04.2002 - Released - DefKey: 7009