



Clear Disc Hitag S - 30 mm

Chip type:	Hitag S – read / write 2kbits, 256 bits, or read only 32 bits	* Test conditions and remarks
Physical:	Diameter:	30 mm ± 0.5 mm
	Thickness:	0.6 mm ± 0.2 mm
	Material:	Polyethylen + Polyester (outside)
	Color:	Transparent
Electrical:	Operating frequency:	125 kHz ± 6 kHz
		* At room temperature
Thermal:	Storage:	-20°C to +60°C
	Operating:	-20°C to +60°C
		* 1x 1000h
Part number:	621117 for Hitag S 32, 623117 for Hitag S 256, 624117 for Hitag S 2048	

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.3.82 - V1 - 11.02.2004 - Released - DefKey : 11204

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com