



EPOXY DISC I-Code SL2 50 x 1.6 mm + hole 4.3 mm 13.56 MHz ISO 15693

Chip type:	I-Code SL2 – read / write 1 kbits ISO 15693		* Test conditions and remarks
Physical:	Diameter:	50 mm ± 0.5 mm	
	Thickness:	1.6 mm ± 0.3 mm	
	Centre hole:	4.3 mm	
	Material:	Laminated epoxy with glass fiber	
	Color:	Black	
Electrical:	Operating frequency:	13.56 MHz ± 0.7 MHz	*At room temperature
Chemical:	Water (IP66), Good stability for mineral oil, ethanol, petrol, fuel, etc Refer to the application note "Epoxy chemical stability"		
Thermal:	Storage:	-40°C to +85°C	* 1x 1000h
	Peak:	+140°C	* 1x 24h
	Shock/fatigue:	-25°C to +100°C	* 50x 5min with transposition in 20s
	Operating:	-25°C to +85°C	
Part number:	629154		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.3.94 - V1 - 10.02.2005 - Released - DefKey : 12029

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com