



GLASS TAG 8 mm Q5

Chip type:	Q5 – 264 bits R/W (224 bits user data)		
Physical:	Diameter:	2.12 mm	± 0.1 mm
	Length:	8.0 mm	± 1 mm
	Material:	BIO GLASS 8625	
	Color:	Transparent	
Electrical:	Operating frequency:	140 kHz	
Chemical:	Waterproof according to IP68		
	Resistance to immersion in salt water, alcohol, oil, 10 % HCL and Ammoniac (t= 100 hours)		
Mechanical:	Shock:	IEC 68-2-29	
	Vibration:	IEC 68-2-6	
Thermal:	Storage range :	-40°C to	90 °C Up to 1000 hours
	Operating range:	0 °C to	50 °C
Part number:	612202	All coded with Dec Code 1234567890	
	612204	All coded with Dec Code 1234567890 with parylene coating	
Remark:	Configuration of 612202 and 612204 is ASK-Manchester-64 bits Unlocked Data.		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.4.19 - V5 - 16.07.2004 - Released - DefKey : 11596

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com