



ISO Card MIFARE

Description	Configurable, flexible white-white ISO card with 1 kbytes data memory design to suit to most 13.56 MHz applications.		
IC type:	MIFARE Standard MF1 S50.		
Physical:	Thickness :	0.80 mm	± 0.06 mm
	Length:	85.60 mm	± 0.12 mm
	Width:	53.98 mm	± 0.05 mm
	Weight :	5.30 g	± 0.50 g
	Color :	White / white	
Transport keys:	KEY A FF FF FF FF FF FF KEY B FF FF FF FF FF FF		
Printing:	Both side are full printable with offset, thermo-transfer and dye sublimation printing.		
Contact module:	Customer may embed a contact module at ISO position.		
Magnetic stripe:	Optional HICO 2750 Oe magnetic stripe in ISO position.		
Electrical::	Operating Frequency:	13.56MHz	
Material:	PVC, white / white (Glossy).		
Thermal:	-35°C and +50 °C	(-30 °F and +122 °F)	according to ISO 7816 .
Resistance:	The card is designed to resist common stress known from public transportation and crypto payments environments.		
Parts number:	W/O magn. Stripe: 607401 / 2750 Oe magn. Stripe: 607402		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.2.7 - V2 - 05.10.2004 - Released - DefKey : 11767

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com