



ISO Card With 2 punch marks

Description	Proximity ISO card, flexible Card design to suit to most 125 kHz proximity systems.		
IC type:	UNIQUE / Q5 / TITAN / HTS256 / HTS2048		
Physical:	Thickness:	0.76 mm	± 0.08 mm
	Length:	85.60 mm	± 0.12 mm
	Width:	53.98 mm	± 0.05 mm
	Weight:	5.60 g	± 0.50 g
	Color:	White / white	
Printing:	Both side are full printable with offset, thermo-transfer and dye sublimation printing.		
Marking:	1 punch mark on long side and 1 punch mark on small side of the card. Marks positioned at 6±0.03mm from the edge of the card and centered. Punch slot recommended size : 3.18 x 14.3mm		
Contact module:	Customer may embed a contact module at ISO position.		
Magnetic stripe:	Optional HICO 2750 Oe magnetic stripe in ISO position.		
Electrical:	Operating Frequency:	125 kHz	± 6 kHz
Material:	PVC, white / white (Glossy).		
Thermal:	-35°C and +50 °C	(-30 °F and +122 °F)	according to ISO 7816 .
Resistance:	The card is designed to resist common stress known from access control and time attendance systems.		
Specials:	Different HICO and LOCO magnetic stripe are available on request as well as customized logo prints and holograms.		
Part number:	Unique W/O magn. Stripe: 601401-288 / 2750 Oe magn. Stripe: 601402-288 Q5 W/O magn. Stripe: 612401-288 / 2750 Oe magn. Stripe: 612402-288 Titan W/O magn. Stripe: 602401-288 / 2750 Oe magn. Stripe: 602402-288 HTS256 W/O magn. Stripe: 623401-288 / 2750 Oe magn. Stripe: 623402-288 HTS2048 W/O magn. Stripe: 624401-288 / 2750 Oe magn. Stripe: 624402-288		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.2.1 - V1 - 27.10.2004 - Released - DefKey : 11822

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com