



## ISO Cards UNIQUE Thermo rewritable

<b>Description</b>	<b>Thermo ReWritable, flexible ISO card design to suit to most 125 kHz proximity systems.</b>		
<b>IC type:</b>	UNIQUE 64 bits RF/64 ASK Manchester		
<b>Physical:</b>	Thickness:	0.76 mm	± 0.08 mm
	Length:	85.60 mm	± 0.12 mm
	Width:	53.98 mm	± 0.05 mm
	Weight:	6.10 g	± 0.50 g
	Color:	White / white	
<b>Thermo rewrite:</b>	Position:	Magnetic stripe area and magnetic stripe dimension (drawing on request).	
	Material:	TRGT33Tab from Mitsubishi Paper Mills Limited	
	Rewrite cycles:	500	
	Printing colors:	Black & Blue	
	Printer example:	CLEARjet GmbH / www.clearjet.com	
<b>Printing:</b>	Both sides are full printable with offset, thermo-transfer and dye sublimation printing.		
<b>Slots:</b>	Three different positions for slots are available.		
<b>Contact module:</b>	Customer may embed a contact module at ISO position.		
<b>Electrical:</b>	Operating Frequency:	125 kHz	± 6 kHz
	<b>Material:</b>	PVC, white / white (Glossy).	
<b>Thermal:</b>	-35°C and +50°C	(-30°F and +122°F)	according to <b>ISO 7816</b> .
<b>Resistance:</b>	The card is designed to resist common stress known from access control and time attendance systems.		
<b>Parts number:</b>	<b>601405</b>		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.  
CLF 3.3.2.18 - V1 - 06.12.2002 - Released - DefKey : 9443

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com