



WRIST BAND Hitag 1

Chip type:	HITAG 1 – 2kbit R/W		* Test conditions and remarks
Physical:	Dimension:	32 x 42 mm	
	Thickness:	5 mm	
	Band length :	250 mm	
	Material:	ABS and water resistant perlon band	
	Color:	Black	
Electrical:	Operating frequency:	125 kHz ± 6 kHz	* At room temperature
Chemical:	Water immersion IP67		* 20°C, 35min, 1m
Thermal:	Storage:	-25°C to +80 °C	
	Operating:	-25°C to +50 °C	
Part number:	608042 (upon request)		

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.
CLF 3.3.2.25 - V3 - 17.03.2003 - Released - DefKey : 9771

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL info@sokymat.ch, WEB www.sokymat.com