



## WRIST BAND Hitag S

<b>IC type:</b>	R/W 256 bits	R/W 2048 bits
<b>Physical:</b>	Dimension:	32 x 42 mm
	Thickness:	5 mm
	Band length :	250 mm
	Material:	ABS and water resistant perlon band
	Color:	Black
<b>Electrical:</b>	Operating frequency:	125 kHz $\pm$ 6 kHz * At room temperature
<b>Chemical:</b>	Water immersion IP67 (IEC 60529)	* 20°C, 35min, 1m
<b>Thermal:</b>	Storage:	-25°C to +80 °C
	Operating:	-25°C to +50 °C
<b>Parts number:</b>	<b>623042</b> for the 256 bits <b>624042</b> for the 2048 bits	
<b>Remark:</b>	More details are available on Philips' Hitag S specification	<a href="http://www.semiconductors.philips.com/markets/identification/">http://www.semiconductors.philips.com/markets/identification/</a>

© SOKYMAT reserves the right to change any information or data in this document without prior notice. The distribution and the update of this document is not controlled. SOKYMAT declines all responsibility for the use of products with any other specifications but the ones mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification.  
CLF 3.3.2.33 - V1 - 25.08.2003 - Released - DefKey : 10411

Sokymat SA, Rte Pra-Charbon 27, 1614 Granges, Switzerland, TEL + 41 (0)21 908 0100, FAX + 41 (0)21 908 0101, EMAIL [info@sokymat.ch](mailto:info@sokymat.ch), WEB [www.sokymat.com](http://www.sokymat.com)